



## Canopy

An energy efficient, cost effective linear LED lighting solution.

These lights bars use the latest 4014 LED technology to achieve high output, but with minimal spotting.




## Product features

The 4014's unique structure ensures superior elliptical light output and improved thermal performance over alternative chip designs.

Perfect for linear lighting typical in point of sale displays, the narrow width of the LED means it can be used on boards and tape as narrow as 4mm.

- 150 lumens per Watt
- 3 MacAdam ellipse
- < 90 CRI
- L80 - 63,000 hours
- Superior spectral performance



**Ara canopy polar curve**

# Canopy

Product	Description	Length (mm)	Wattage (W)	Colour (K)	CRI	Lumens
LBAR-LED-CAN-1205-003-NW	24V BFL BK 1205mm 21W Lightbar NW 4000k 500mm Lead	1205	21	4000	80+	3000
LBAR-LED-CAN-1205-003-WW	24V BFL BK 1205mm 21W Lightbar WW 3000k 500mm Lead	1206	21	3000	80+	2980
LBAR-LED-CAN-1205-002-WWR	24V BFL BK 1205mm 19W Lightbar WW/Red 500mm Lead	1207	19	-	80+	2250
LBAR-LED-CAN-1065-002-NW	24V BFL BK 1065mm 18W Lightbar NW 4000k 500mm Lead	1065	18	4000	80+	2647
LBAR-LED-CAN-1065-002-WW	24V BFL BK 1065mm 18W Lightbar WW 3000k 500mm Lead	1066	18	3000	80+	2629
LBAR-LED-CAN-1065-002-WWR	24V BFL BK 1065mm 16W Lightbar WW/Red 500mm Lead	1067	16	-	80+	1985
LBAR-LED-CAN-995-002-NW	24V BFL BK 995mm 17W Lightbar NW 4000k 500mm Lead	995	17	4000	80+	2470
LBAR-LED-CAN-995-002-WW	24V BFL BK 995mm 17W Lightbar WW 3000k 500mm Lead	996	17	3000	80+	2454
LBAR-LED-CAN-995-0022-WWR	24V BFL BK 995mm 15.5W Lightbar WW/Red 500mm Lead	997	15.5	-	80+	1850
LBAR-LED-CAN-855-003-NW	24V BFL BK 855mm 16W DBL Lightbar NW 4000k 500mm Lead	855	16	4000	80+	2117
LBAR-LED-CAN-855-003-WW	24V BFL BK 855mm 16W DBL Lightbar WW 3000k 500mm Lead	855	16	3000	80+	2103
LBAR-LED-CAN-855-002-WWR	24V BFL BK 855mm 14.5W Lightbar WW/Red 500mm Lead	855	14.5	-	80+	1560

## Features



**Gear Tray**



**Magnet**



**Loom**



**Lead**

## Accreditations

