

Ara



Slim

An energy efficient, cost effective linear slim LED lighting solution for applications where space is restricted.




Product features

The 4014's unique structure ensures superior elliptical light output and improved thermal performance over alternative chip designs.

Perfect for linear lighting typical in point of sale displays, the narrow width of the LED means it can be used on boards and tape as narrow as 4mm.

- 150 lumens per Watt
- 3 MacAdam ellipse
- < 90 CRI
- L80 - 63,000 hours
- Superior spectral performance



Ara slim polar curve

Slim

Product	Description	Length (mm)	Wattage (W)	Colour (K)	CRI	Lumens
LBAR-LED-SLIM-1205-001-30	24V MG BK 1205mm 6.5W Slim Lightbar 3000K BLK 650mm MG lead	1205	6.5	3000	80+	895
LBAR-LED-SLIM-1205-001-40	24V MG BK 1205mm 6.5W Slim Lightbar 4000K BLK 650mm MG lead	1205	6.5	4000	80+	965
LBAR-LED-SLIM-1065-001-30	24V MG BK 1065mm 6.2W Slim Lightbar 3000K BLK 650mm MG lead	1065	6.2	3000	80+	790
LBAR-LED-SLIM-1065-001-40	24V MG BK 1065mm 6.2W Slim Lightbar 4000K BLK 650mm MG lead	1065	6.2	4000	80+	850
LBAR-LED-SLIM-995-001-30	24V MG BK 995mm 5.7W Slim Lightbar 3000K BLK 650mm MG lead	995	5.7	3000	80+	735
LBAR-LED-SLIM-995-001-40	24V MG BK 995mm 5.7W Slim Lightbar 4000K BLK 650mm MG lead	995	5.7	4000	80+	800
LBAR-LED-SLIM-855-001-30	24V MG BK 855mm 5W Slim Lightbar 3000K BLK 650mm MG lead	855	5	3000	80+	630
LBAR-LED-SLIM-855-001-40	24V MG BK 855mm 5W Slim Lightbar 4000K BLK 650mm MG lead	855	5	4000	80+	680

Features



Gear Tray



Magnet



Loom



Lead

Accreditations

