


# Downlight DE1

LED downlight



## Key features

- Material: Aluminium
- Nominal lumens: 1950lm, 2600lm
- CCT: 2700K, 3000K, 4000K
- Beam angle: 20°, 30°, 50°
- 50,000 hours
- Warranty: 5 years
- Colour: White
- Control: DALI, Analogue, Phase



  $\varnothing 115\text{mm}$

## Accessories

Clear lens

Honeycomb louvre

## Product information and code selector

| Product Code | COB  | Code | Nominal lumens (lm) | Code     | Kelvin (K)           | Code           | CRI | Code | Beam angle        | Code           | Colour | Code | Control                              | Code                 | Accessories                    | Code     |
|--------------|------|------|---------------------|----------|----------------------|----------------|-----|------|-------------------|----------------|--------|------|--------------------------------------|----------------------|--------------------------------|----------|
| DE1          | Cree | CR   | 1950<br>2600        | 20<br>26 | 2700<br>3000<br>4000 | 27<br>30<br>40 | 80  | 80   | 20°<br>30°<br>50° | 20<br>30<br>50 | White  | WH   | Non Dim<br>DALI<br>Analogue<br>Phase | ND<br>DL<br>AN<br>PH | Clear lens<br>Honeycomb louvre | CL<br>HC |

Code builder example : **DE1 CR 20 27 80 20 WH ND CL**

(DE1 = Downlight DE1. CR = Cree chip. 20 = 1950lm. 27 = 2700K. 80 = 80 CRI. 20 = 20 deg. WH = White. ND = Non Dim. CL = Clear lens.)

**Note only one accessory can be fitted.**

### Additional emergency options\*

| Emergency option    | Code |
|---------------------|------|
| Standard emergency  | EM   |
| Emergency self test | EST  |
| DALI emergency      | EDL  |

**\*Please add the code to the end**