

# ADFLEX 2216

Flexible LED strip system

## Key features

- Operating voltage (V): 12V or 24V DC
- Beam angle: 120 degree
- Driver type: Constant voltage
- Operating temperature (range): -20° to 60°C
- CRI: >90
- IP rating: IP20
- High R9 value
- Variable cut points

### Suitable for:

- Header / graphic illumination
- Cabinet
- Refrigeration
- Wall washers
- Canopy lighting
- Hotels
- Office

## Product information and code selector

Product code	Voltage (V)	LEDs p/metre	Wattage (W)	Colour (K)	Lumens / metre (lm/m)	LED efficiency (lm/W)	Cut point (mm)
AF2216-12-60-30	12	60	4.8	3000	384	80	50
AF2216-12-60-40	12	60	4.8	4000	408	85	50
AF2216-12-60-60	12	60	4.8	6000	417	87	50
AF2216-12-120-30	12	120	9.6	3000	768	80	25
AF2216-12-120-40	12	120	9.6	4000	816	85	25
AF2216-12-120-60	12	120	9.6	6000	816	85	25
AF2216-12-180-30	12	180	14.4	3000	1152	80	16.67
AF2216-12-180-40	12	180	14.4	4000	1180	82	16.67
AF2216-12-180-40	12	180	14.4	6000	1180	82	16.67
AF2216-12-240-30	12	240	19.2	3000	1497	78	12.5
AF2216-12-240-40	12	240	19.2	4000	1536	80	12.5
AF2216-12-240-60	12	240	19.2	6000	1574	82	12.5
AF2216-24-70-30	24	70	4.8	3000	456	95	100
AF2216-24-70-40	24	70	4.8	4000	504	102	100
AF2216-24-70-60	24	70	4.8	6000	504	102	100
AF2216-24-140-30	24	140	9.6	3000	912	95	50
AF2216-24-140-40	24	140	9.6	4000	960	100	50
AF2216-24-140-60	24	140	9.6	6000	979	102	50
AF2216-24-210-30	24	210	14.4	3000	1368	95	33.33
AF2216-24-210-40	24	210	14.4	4000	1468	102	33.33
AF2216-24-210-60	24	210	14.4	6000	1468	102	33.33
AF2216-24-280-30	24	280	19.2	3000	1748	91	25
AF2216-24-280-40	24	280	19.2	4000	1844	96	25
AF2216-24-280-60	24	280	19.2	6000	1901	99	25