

Luminaire Data Sheet


Aquila



Traditional corrosion proof luminaire suitable for a range of industrial applications.
PC body, UV stabilised PC diffuser
Options with integral emergency
Options with integral PIR or MW control



- Available in 1200mm & 1500mm lengths
- Up to 147 lumens per Watt
- 4000K CCT
- Operating temperature (range): -10° to +40°C (Emergency variants: 0° to +40°C)
- IP65, IK08
- L70, 50,000 hours
- 5 year warranty



Code	Description	Luminaire Lumens	Luminaire Lumens Emergency	Inrush Current	Current (A)	Qty Type C 10A breaker	Dimensions L x W x H (mm)
AQ12-281940-OP	Aquila 1200, 230V, 19W	2793	184	5.2A / 47µs	0.08	40	1190 x 73 x 75
AQ12-503640-OP	Aquila 1200, 230V, 36W	5013	186	5.6A / 47µs	0.16	21	1190 x 95 x 75
AQ15-412940-OP	Aquila 1500, 230V, 29W	4116	182	5.2A / 47µs	0.12	27	1490 x 73 x 75
AQ15-694740-OP	Aquila 1500, 230V, 47W	6945	179	6.9A / 58µs	0.20	16	1490 x 95 x 75