

Wallpack- Aries

Data sheet

Key technical attributes include:

- Colour temperature 4000°K
- Operating temperature (range): -10° to +40°C
- CRI: >80
- Sealed to IP65, with IK08 impact resistance
- L70 50,000 hours
- Warranty 5 Years
- Power: 16Watts
- 3hr emergency option available
- Microwave presence sensor available



Product Name	Aries			
Advance Part Code	KM1 11 40 80 WH ND	KM1 11 40 80 WH ND EM	KM1 11 40 80 WH ND MW	KM1 11 40 80 WH ND MW EM
Description	Circular amenity, polycarbonate housing in white, opal diffuser, non-dim	Circular amenity, polycarbonate housing in white, opal diffuser, non-dim, c/w 3hr emergency	Circular amenity, polycarbonate housing in white, opal diffuser, non-dim c/w microwave sensor	Circular amenity, polycarbonate housing in white, opal diffuser, non-dim c/w microwave sensor and 3hr emergency
Nominal Voltage (V)	230	230	230	230
Power (W)	16	16	16	16
Lumen Output	1627	1627	1627	1627
Lumens/Watt	101.6	101.6	101.6	101.6
Life Expectancy	50,000 hours L70	50,000 hours L70	50,000 hours L70	50,000 hours L70
CCT (K)	4000	4000	4000	4000
CRI	>80	>80	>80	>80
Macadam Ellipses	<3	<3	<3	<3
Power Factor	>0.8	>0.8	>0.8	>0.8
Running Current (A)	0.07	0.07	0.07	0.07
Inrush Current	20A for 195uS	20A for 195uS	20A for 195uS	20A for 195uS
Insulation Class	NA	NA	NA	NA
IP rating	IP65	IP65	IP65	IP65
IK rating	IK08	IK08	IK08	IK08
Qty per Type C 10A breaker	48	48	48	48
Operating Temperature	-10 to +40°C	-10 to +40°C	-10 to +40°C	-10 to +40°C
Warranty	5 years	5 years	5 years	5 years
Gross Weight (kg)	1.4	1.7	1.4	1.7
Nett Weight (kg)	0.9	1.2	0.9	1.2

Diameter: 320mm Depth: 100mm

