

Wallpack – Fornax

Data sheet

Key technical attributes include:

- Colour temperature 4000°K
- Operating temperature (range): -20° to +25°C
- IP rating: IP65, Impact rating: IK08
- L70 50,000 hours
- Warranty 3 Years
- Photocell and emergency options available



	Fornax	Fornax	Fornax
Advance Part code	WP1 40 40 280	WP1 40 40 280 PC	WP1 40 40 280 PC EM
Description	Wall pack, 39 Watts, 4000K, 2600 lumens, black	Wall pack, 39 Watts, 4000K, 2600 lumens, black, with photocell	Wallpack, 39 Watts, 4000K, 2600 lumens, black, with photocell, emergency version
Nominal voltage (V)	230	230	230
Power	39	39	39
Lumen output	2800	2800	2800
Lumens/Watt	71.8	71.8	71.8
Life expectancy	50,000 hours to L70	50,000 hours to L70	50,000 hours to L70
Colour temperature	4000°K	4000°K	4000°K
CRI	>80	>80	>80
Macadam ellipses	<6	<6	<6
Power factor	>0.95	>0.95	>0.95
Running Current (A)	0.17	0.17	0.17
Inrush Current	16 amps for 100uS	16 amps for 100uS	16 amps for 100uS
Emergency lumen output	N/A	N/A	130
Insulation class	1	1	1
IP rating	IP65	IP65	IP65
IK rating	IK08	IK08	IK08
Qty type C 10 amp breaker	20	20	20
Operating temperature	-20 to +25°C	-20 to +25°C	-20 to +25°C
Warranty (Years)	3	3	3
Gross weight	1.9	1.9	2.2
Nett weight	1.4	1.4	1.7

