

Wallpack – Octans

Data sheet

Key technical attributes include:

- Wattage 13/18/28 Watts
- Lumen output 1700/2500/3500 switched
- Operating temperature (range): -20° to +40°C
- IP rating: IP65, Impact rating: IK10
- L70 60,000 hours
- Warranty 5 Years
- Photocell and emergency options available



	Octans	Octans
Advance Part code	WP2 35 28 40 AN	WP2 35 28 40 AN EM
Description	Wallpack, 13/18/28 Watts, 4000K, 1700/2500/3500 lumens, anthracite.	Wallpack, 13/18/28 Watts, 4000K, 1700/2500/3500 lumens, anthracite, emergency
Nominal voltage (V)	230	230
Power	13/18/28w	13/18/28w
Lumen output	3500	3500
Lumens/Watt	125.0	125.0
Life expectancy	60,000 hours to L70	60,000 hours to L70
Colour temperature	4000°K	4000°K
CRI	80	80
Macadam ellipses	<6	<6
Power factor	>0.9	>0.9
Running Current (A)	0.12	0.12
Inrush Current	10amps for 100uS	10amps for 100uS
Emergency lumen output	N/A	275
Insulation class	1	1
IP rating	65	65
IK rating	10	10
Qty type C 10 amp breaker	24	24
Operating temperature	-20 to +40°C	-20 to +40°C
Warranty (Years)	5	5
Gross weight	2.7	3.25
Nett weight	2.3	3

