

Bollards- Colomba

Data sheet

Key technical attributes include:

- 80 Lumens/Watt
- CRI: >80
- IP rating: IP65
- L70 34,000 hours
- Warranty 3 Years
- 3-hour emergency version available
- 3000 or 4000°K colour temperature



Product Name	BL1 Bollard	BL1 Bollard	BL1 Bollard	BL Root
Product name	Colomba	Colomba	Colomba	Colomba
Advance Part code	BL1 20 25 3040 BL DOME	BL1 20 25 3040 BL FLAT	BL1 90 25 3040 BL LOUVRE	BL ROOT
Description	Bollard, dome head, 1 metre tall, 25 Watts, 3000/4000K, 2000 lumens, black	Bollard, flat head, 1 metre tall, 25 Watts, 3000/4000K, 2000 lumens, black	Bollard, flat head with louvre, 1 metre tall, 25 Watts, 3000/4000K, 875 lumens, black	Root mounting kit for BL1 Bollards
Nominal Voltage (V)	230	230	230	N/A
Power (W)	25	25	25	N/A
Lumen output	2000	2000	875	N/A
Lumens /Watt	80	80	35	N/A
Life expectancy	34,000 hours to L70	34,000 hours to L70	36,000 hours to L70	N/A
Colour temperature (°K)	3000/4000	3000/4000	3000/4000	N/A
CRI	>80	>80	>80	N/A
Macadam ellipses	<6	<6	<6	N/A
Power factor	>0.95	>0.95	>0.95	N/A
Running Current (A)	0.11	0.11	0.11	N/A
Inrush Current	20 amps max	20 amps max	20 amps max	N/A
Insulation Class	1	1	1	N/A
IP rating	IP65	IP65	IP65	N/A
IK rating	IK09	IK09	IK09	N/A
Qty type C 10 amp breaker	24	24	24	N/A
Operating temperature	-20 to +45°C	-20 to +45°C	-20 to +45°C	N/A
Warranty	3 years	3 years	3 years	3 years
Gross weight (Kg)	6.25	6.25	6.25	6.25
Nett weight (Kg)	5.25	5.25	5.25	5.25



