

Advance LED Lighting Solutions new Lorem emergency bulkhead is an IP65 surface mounted luminaire built for lighting large industrial areas. The Lorem can be surface mounted or semi-recessed and is ideal for applications where higher illuminance is required with it's output being able to switch between 1000 lumens and 1500 lumens depending on the required application. With it's high ingress protection rating it is perfectly suited for use as an final exit bulkhead to provide further emergency lighting even after a building has been evacuated. The Lorem features a lithium iron battery and is built with an open-area lighting channel that is perfect for reducing the amount of fittings needed to sufficiently light a space to meet emergency lighting criteria.



Key features

- Colour temperature 6500°K
- Operating temperature (range): +5° to +35°C
- CRI: >80
- IP rating: IP65
- L70 50,000 hours
- Warranty 5 Years
- Wattage: 10W
- Lumen output: 1000/1500 lumens
- Impact Rating: IK10



Product information and code selector

Product code	Optic	Code	Installation Method	Code	Test Option	Code	Lumen Output	Code
EM	Open	BULK2	Surface Mounted	SUR	Manual Test	MT	1000lm	LO
EM	Open	BULK2	Surface Mounted	SUR	Self Test	ST	1000lm	LO
EM	Open	BULK2	Surface Mounted	SUR	Manual Test	MT	1500lm	HI
EM	Open	BULK2	Surface Mounted	SUR	Self Test	ST	1500lm	HI

