

Highbay - Leo

Data sheet

Key technical attributes include:

- Colour temperature 5000°K
- Operating temperature (range): -25° to +45°C
- CRI: >80
- IP rating: IP65, Impact rating: IK08
- L70 54,000 hours
- Warranty 5 Years
- Wattage: 100W, 150W & 200W



	Leo	Leo	Leo
Advance Part code	HB3 13 10 50 BL AR	HB3 20 15 50 BL AR	HB3 26 20 50 BL AR
Description	Highbay, 100 Watts, 5000K, 13,000 lumens, non-dimmable, area optic	Highbay, 150 Watts, 5000K, 19500 lumens, non-dimmable, area optic	Highbay, 200 Watts, 5000K, 26,000 lumens, non-dimmable, area optic
Nominal Voltage (V)	230	230	230
Power (W)	100	150	200
Lumen output	13000	19500	26000
Lumens/Watt	130	130	130
Life expectancy	54,000 Hours to L70	54,000 Hours to L70	54,000 Hours to L70
Colour temperature (°K)	5000	5000	5000
CRI	80	80	80
Macadam ellipses	<6	<6	<6
Power factor	0.95	0.95	0.95
Running Current (A)	0.43	0.65	0.87
Inrush current	65A for 500µs	65A for 500µs	65A for 500µs
Insulation class	1	1	1
IP rating	65	65	65
IK rating	8	8	8
Qty type C 10- amp breaker	9	5	4
Operating temperature	-25 to +45°c	-25 to +45°c	-25 to +45°c
Warranty	5 Years	5 Years	5 Years
Gross weight (Kg)	2.1	3.1	4
Nett weight (Kg)	1.7	2.7	3.2

