

Emergency bulkhead – Lorem

Data sheet

Key technical attributes include:

- Lumen output selectable 1000 or 1500 lumens
- Operating temperature (range): +5° to +45°C
- IP rating: IP65,
- Impact rating: IK08
- Self-test version available
- Lithium Iron battery as standard
- Wattage: 10W running, 4.5W charging
- Colour temperature 6500°K
- Warranty 5 Years



Product name	Lorem	Lorem
Advance Part code	EMBULK2 SUR MT (LO-HI)	EMBULK2 SUR ST (LO-HI)
Description	IP65 High output emergency bulkhead, surface mounted, 10W, 1000/1500 lumens switchable, white, 3 hour non-maintained complete with Lithium Iron batteries.	IP65 High output emergency bulkhead, complete with self test function, surface mounted, 10W, 1000/1500 lumens switchable, white, 3 hour non-maintained complete with Lithium Iron batteries.
Nominal Voltage (V)	230	230
Power	4.5W Charging, 10W running	4.5W Charging, 10W running
Lumen output	1000/1500	1000/1500
Life expectancy	>50,000 hours	>50,000 hours
Colour temperature	6500°K	6500°K
CRI	80	80
Macadam ellipses	<6	<6
Power factor	>0.3	>0.3
Inrush current	12.8A for 100uS	12.8A for 100uS
Emergency lumen output	1000/1500	1000/1500
Insulation Class	2	2
IP rating	65	65
IK rating	8	8
Qty C 10 amp breaker	20	20
Operating temperature	+5 to +45°C	+5 to +45°C
Warranty period	Luminaire 5 years Battery 2 years	Luminaire 5 years Battery 3 years

