

LED Panel- Lynx

Data sheet

Key technical attributes include:

- Up to 139 lumens/Watt
- 25, 30 or 36W versions available
- CRI: >80
- L70 50,000 hours
- Warranty 3 Years
- Low glare panel
- 4000°K colour temperature



Product Name	PC8 LED Panel	PC8 LED Panel	PC8 LED Panel	PC8 LED Panel	PC8 LED Panel	PC8 LED Panel
Product name	Lynx	Lynx	Lynx	Lynx	Lynx	Lynx
Advance Part code	PC8 35 25 40 WH ND	PC8 35 25 40 WH DD	PC8 36 30 40 WH ND	PC8 36 30 40 WH DD	PC8 38 36 40 WH ND	PC8 38 36 40 WH DD
Description	LED modular low glare panel, 600 x 600mm, 3500 lumens, 25Watts, 4000K, 80 CRI, Non Dimmable	LED modular low glare panel, 600 x 600mm, 3500 lumens, 25Watts, 4000K, 80 CRI, DALI Dimmable	LED modular low glare panel, 600 x 600mm, 3600 lumens, 30Watts, 4000K, 80 CRI, Non Dimmable	LED modular low glare panel, 600 x 600mm, 3600 lumens, 30Watts, 4000K, 80 CRI, DALI Dimmable	LED modular low glare panel, 600 x 600mm, 3800 lumens, 36Watts, 4000K, 80 CRI, Non Dimmable	LED modular low glare panel, 600 x 600mm, 3800 lumens, 36Watts, 4000K, 80 CRI, DALI Dimmable
Nominal Voltage (V)	230	230	230	230	230	230
Power (W)	25	25	30	30	36	36
Lumen output	3463	3405	3570	3510	3755	3740
Lumens/Watt	138.52	136.20	119.00	117.00	104.31	103.89
Life expectancy	50,000 hours to L70	50,000 hours to L70	50,000 hours to L70	50,000 hours to L70	50,000 hours to L70	50,000 hours to L70
Colour temperature	4000°K	4000°K	4000°K	4000°K	4000°K	4000°K
CRI	80	80	80	80	80	80
Macadam ellipses	<6	<6	<6	<6	<6	<6
Power factor	>0.9	>0.9	>0.9	>0.9	>0.9	>0.9
Inrush current	25A	16A	27A	16A	38A	16A
Running Current (A)	0.109	0.109	0.130	0.130	0.157	0.157
Emergency lumen output	N/A	N/A	N/A	N/A	N/A	N/A
Insulation Class	2	2	2	2	2	2
IP rating	IP40	IP40	IP40	IP40	IP40	IP40
IK rating	IK08	IK08	IK08	IK08	IK08	IK08
Qty type C 10 amp breaker	23	23	24	24	20	20
Operating temperature	-20 to +40°C	-20 to +40°C	-20 to +40°C	-20 to +40°C	-20 to +40°C	-20 to +40°C
Warranty	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years
Gross weight (Kg)	3.8	3.8	3.8	3.8	3.8	3.8
Nett Weight (Kg)	2.9	2.9	2.9	2.9	2.9	2.9

