

# Linear - Tucana

## Data sheet

Key technical attributes include:

- Wattage: 25 or 45W
- 3400 or 6200 lumen output
- 136 lumens/watt
- Colour temperature 4000°K
- Operating temperature (range): -20° to +40°C
- CRI: >80
- L70 60,000 hours
- Warranty 5 Years



Product name	Tucana	Tucana	Tucana	Tucana
Advance Part code	BC3 34 25 40 WH ND	BC3 34 25 40 WH EM	BC3 62 45 40 WH ND	BC3 62 45 40 WH EM
Description	Linear LED fitting, Opal diffuser, 1500mm, 3400 lumens, 25W, 4000K, 80 CRI, white, non-	Linear LED fitting, Opal diffuser, 1500mm, 3400 lumens, 25W, 4000K, 80 CRI, white, non-	Linear LED fitting, Opal diffuser, 1500mm, 6200 lumens, 45W, 4000K, 80 CRI, white, non-	Linear LED fitting, Opal diffuser, 1500mm, 6200 lumens, 45W, 4000K, 80 CRI, white, non-
Nominal Voltage (V)	230	230	230	230
Power (W)	25	25	45	45
Lumen output	3400	3400	6200	6200
Lumens/watt	136.00	136.00	137.78	137.78
Life expectancy	60,000 hours to L70	60,000 hours to L70	60,000 hours to L70	60,000 hours to L70
Colour temperature (°K)	4000	4000	4000	4000
CRI	81	82	83	84
Macadam ellipses	<6	<6	<6	<6
Power factor	>0.9	>0.9	>0.9	>0.9
Running Current (A)	0.11	0.11	0.20	0.20
Inrush current	5.5amps for 20uS	5.5amps for 20uS	15A for 100uS	15A for 100uS
Insulation Class	1	1	1	1
IP rating	IP20	IP20	IP20	IP20
IK rating	IK03	IK03	IK03	IK03
Qty type C 10 amp breaker	21	21	17	17
Operating temperature	-20 to +40°C	0 to +40°C	-20 to +40°C	0 to +40°C
Warranty	5 Years	5 Years	5 Years	5 Years
Gross weight (Kg)	7.4	8.8	7.4	8.8
Nett weight (Kg)	6.9	8.4	6.9	8.4

