

Wallpack- Vela

Data sheet

Key technical attributes include:

- 22 or 27 Watts
- 1680 or 2850 lumen output
- IP rating: IP20
- L70 60,000 hours
- Warranty 5 Years
- 3000 or 4000°K colour temperature
- 3-hour emergency back-up option



Product Name	Vela	Vela	Vela	Vela
Part code	WP4 16 22 40 WH ST	WP4 16 22 40 WH EM	WP4 28 27 40 WH ST	WP4 28 27 40 WH EM
Description	Circular decorative wallpack, suitable for wall or ceiling mount with white bezel, diameter 335mm. Power 22W, 1680lumens, 3/4000°K colour temperature, non-dimmable.	Circular decorative wallpack, suitable for wall or ceiling mount with white bezel, diameter 335mm. Power 22W, 1680lumens, 3/4000°K colour temperature, non-dimmable, complete with emergency pack.	Circular decorative wallpack, suitable for wall or ceiling mount with white bezel, diameter 435mm. Power 27W, 2850 lumens, 3/4000°K colour temperature, non-dimmable.	Circular decorative wallpack, suitable for wall or ceiling mount with white bezel, diameter 435mm. Power 27W, 2850 lumens, 3/4000°K colour temperature, non-dimmable, complete with emergency pack.
Nominal voltage (V)	230	230	230	230
Power	22	22	27	27
Lumen output	1680	1680	2850	2850
Lumens/Watt	76.4	76.4	105.6	105.6
Life expectancy	60,000 Hours to L70	60,000 Hours to L70	60,000 Hours to L70	60,000 Hours to L70
Colour temperature	3/4000°K	3/4000°K	3/4000°K	3/4000°K
CRI	80	80	80	80
Macadam ellipses	<6	<6	<6	<6
Power factor	0.9	0.9	0.95	0.95
Running Current (A)	0.10	0.10	0.12	0.12
Inrush Current	8Amps for 80µS	8Amps for 80µS	8Amps for 80µS	8Amps for 80µS
Emergency lumen output	N/A	150	N/A	165
Insulation class	1	1	1	1
IP rating	20	20	20	20
IK rating	7	7	7	7
Qty type C 10 amp breaker	25	25	21	21
Operating temperature	-10 to +40°C	5 to +40°C	-10 to +40°C	5 to +40°C
Warranty	5 years	5 years	5 years	5 years
Gross weight	1.54	1.79	2.1	2.3
Nett weight	1.44	1.69	1.9	2.1

