Emergency – Evadere

Data sheet

Key technical attributes include:

- 3-hour emergency duration
- Operating temperature (range): 5° to +45°C
- Lithium iron battery
- 120/130 Lumen output
- Self-test version available
- Available in black
- Warranty 5 Years





	EM Spot 1	EM Spot 2	EM Spot 1
Product name	Evadere	Evadere	Evadere
Advance Part code	EM SPOT1 REC	EM SPOT1 REC ST	EM SPOT1 REC BK
Description	Emergency spot downlight, 1W, 120/130 lumens, recessed, white	Emergency spot downlight, 1W, 120/130 lumens, recessed, white, LiFe battery, complete with self test function.	Emergency spot downlight, 1W, 120/130 lumens, recessed, black
Nominal Voltage (V)	230	230	230
Power (W)	1	1	1
Life expectancy	36,000 hours to L70	36,000 hours to L70	36,000 hours to L70
Colour temperature (°K)	6500°K	6500°K	6500°K
CRI	80	80	80
Power factor	0.34	0.34	0.34
Running Current (A)	0.01	0.01	0.01
Inrush current (A)	3	3	3
Emergency lumen output	120 lumens area, 130 corridor	120 lumens area, 130 corridor	120 lumens area, 130 corridor
Insulation Class	2	2	2
IP rating	20	20	20
Qty C 10 amp breaker	30	30	30
Operating temperature	5 to +45°C	5 to +45°C	5 to +45°C
Warranty	Product 5 Years, battery 2 years	Product 5 Years, battery 2 years	Product 5 Years, battery 2 years
Gross weight	0.4	0.4	0.4
Nett weight	0.35	0.35	0.35





