

Post Top – Hercules

Key technical attributes include:

- Wattage: 19, 26, 34, & 41Watt
- 2600 to 5200 Lumens
- Up to 140 Lumens/Watt
- Colour temperature 4000°K
- Die cast aluminium body
- Polycarbonate diffuser
- Operating temperature range: -25° to +40°C
- IP rating: IP65, Impact rating: IK08
- Warranty 5 Years



Product name	Hercules	Hercules	Hercules	Hercules	
Advance Part code	PT21001GR	PT21002GR	PT21003GR	PT21004GR	FLCONNECT01
Description	Decorative post top lantern, car park optic, 19 Watts, 3000 lumens, 4000K, dark grey body, 60 or 76mm entry.	Decorative post top lantern, car park optic, 26 Watts, 3600 lumens, 4000K, dark grey body, 60 or 76mm entry.	Decorative post top lantern, car park optic, 34 Watts, 7500 lumens, 4000K, dark grey body, 60 or 76mm entry.	Decorative post top lantern, car park optic, 41 Watts, 5200 lumens, 4000K, dark grey body, 60 or 76mm entry.	In line power supply connector. IP66 for 3 x 1.5mm ² cable. Push in terminals, 450Volts, 10 amps max
Nominal Voltage (V)	230	230	230	230	450
Power (W)	19	26	34	41	
Lumen output	2655	3617	4521	5195	
Lumens/Watt	139.7	139.1	133.0	126.7	
Life expectancy	100,000 hours to L80B50	100,000 hours to L80B50	100,000 hours to L80B50	100,000 hours to L80B50	
Colour temperature	4000K	4000K	4000K	4000K	
CRI	80	80	80	80	
Power factor	0.95	0.95	0.95	0.95	
Inrush current	5 Amps for 50µS	5 Amps for 50µS	5 Amps for 50µS	5 Amps for 50µS	
Insulation Class	1	1	1	1	
IP rating	IP65	IP65	IP65	IP65	
IK rating	IK08	IK08	IK08	IK08	
Operating temperature	-25 to +40°C	-25 to +40°C	-25 to +40°C	-25 to +40°C	
Supplier warranty (Years)	5	5	5	5	
Nett weight (Kg)	4.9	4.9	4.9	4.9	
Wind area (m ²)	0.0814	0.0814	0.0814	0.0814	

Code	Dimensions (mm)		
	Length (L)	Width (W)	Height (H)
PT2001GR	291	230	58
PT2002GR	338	280	59
PT2003GR	381	312	62
PT2004GR	381	312	62

