

Hercules

Advance LED Lighting Solutions decorative post top, the Hercules, offers a multitude of different lumen outputs to suit a varied range of applications. Manufactured from die-cast aluminium and frosted polycarbonate, the body of the luminaire is dust tight and low pressure water jet proof. Lifetime is 100,000 hours to L80 with output options of 2600 lumens up to 5200 lumens and efficiency up to 140 lumens per Watt.. Supplied in dark grey.



Key features

- Colour temperature 4000°K
- Up to 140 lumens/Watt
- Operating temperature (range): -25° to +40°C
- CRI: >80
- IP rating: IP65
- L80 100,000 hours
- Warranty 5 Years
- Wattage: 19W, 26W, 34W, & 41W
- Impact rating IK08
- 60 or 76mm entry

Product information and code selector

Code	Power (W)	Luminaire Lumens	CCT (K)	Weight (kg)	Optic	Dimensions (mm)		
						Length (L)	Width (W)	Height (H)
PT2001GR	19	2655	4000	5	High efficiency car park optic	291	230	58
PT2002GR	26	3617	4000	5	High efficiency car park optic	338	280	59
PT2003GR	34	4521	4000	5	High efficiency car park optic	381	312	62
PT2004GR	41	5195	4000	5	High efficiency car park optic	381	312	62
FLCONNECT01	N/A	N/A	N/A	N/A	IP66 10 amp mains connector			

FLCONNECT01

