

Luminaire Data Sheet


Hydra Xtreme



Rugged corrosion proof luminaire suitable for aggressive environments.
 PC body, UV stabilised PC diffuser
 Options with through wiring
 Options with DALI control



- Surface mount with clips provided
- Suspension on chain / wire
- 50,000 hrs to L70
- CCT 4000K
- CRI > 80
- IP65, IK10
- SDCM < 3
- Power Factor > 0.9
- Operating Temp -20°C - 40°C
- Insulation Class I
- 5 year warranty



Code	Description	Luminaire Lumens	Inrush Current	Current (A)	Qty Type C 10A breaker	Dimensions L x W x H (mm)
HYX12/302240/OP	Hydra Xtreme 1200, 230V, 22W	3050	5A / 50µs	0.10	33	1175 x 90 x 99
HYX12/413040/OP	Hydra Xtreme 1200, 230V, 30W	4180	5A / 50µs	0.13	25	1175 x 90 x 99
HYX12/604240/OP	Hydra Xtreme 1200, 230V, 43W	6030	5A / 50µs	0.19	17	1175 x 90 x 99
HYX15/372740/OP	Hydra Xtreme 1500, 230V, 27W	3770	5A / 50µs	0.12	27	1455 x 90 x 99
HYX15/523740/OP	Hydra Xtreme 1500, 230V, 37W	5270	5A / 50µs	0.16	20	1455 x 90 x 99
HYX15/755440/OP	Hydra Xtreme 1500, 230V, 54W	7570	5A / 50µs	0.23	14	1455 x 90 x 99
HYX15/997140/OP	Hydra Xtreme 1500, 230V, 71W	9950	5A / 50µs	0.31	10	1455 x 90 x 99