

Designed for retail and commercial interiors, Saber is a range of continuous suspended luminaires offering a striking finished look with clean lines and a contemporary feel. Cutting edge LED technology achieves an impressive efficacy up to 190 lumens per Watt, and the output can be tailored to precise requirements with a comprehensive range of optics. Saber offers a 95,000 hour service life backed by a 5 year warranty



## Key features

- Excellent efficacy, up to 190 lumens per Watt
- 5 year warranty
- 95,000 hours service life to L80/B10
- Through Wired for continuous Lines as Standard
- CCT - 4000K as standard. 3000K also available
- CRI >80

## Order Guide

Code	Power (W)	Luminaire Lumens	CCT (K)	Weight (kg)	Optic	Dimensions (mm)		
						Length	Width	Height
SA11/362240WH-100	22	3678	4000	3.2	extra wide lens	1132	45	65
SA11/513140WH-100	32	5096	4000	3.2	extra wide lens	1132	45	65
SA11/533040WH-100	30	5350	4000	3.2	extra wide lens	1132	45	65
SA11/633640WH-100	36	6362	4000	3.2	extra wide lens	1132	45	65
SA11/734140WH-100	42	7318	4000	3.2	extra wide lens	1132	45	65
SA14/462740WH-100	27	4597	4000	3.5	extra wide lens	1413	45	65
SA14/633940WH-100	39	6370	4000	3.5	extra wide lens	1413	45	65
SA14/663740WH-100	37	6688	4000	3.5	extra wide lens	1413	45	65
SA14/794440WH-100	44	7952	4000	3.5	extra wide lens	1413	45	65
SA14/915140WH-100	52	9147	4000	3.5	extra wide lens	1413	45	65
SA28/925140WH-100	52	9195	4000	5.0	extra wide lens	2818	45	65
SA28/127540WH-100	75	12739	4000	5.0	extra wide lens	2818	45	65
SA28/137340WH-100	73	13376	4000	5.0	extra wide lens	2818	45	65
SA28/168740WH-100	87	15905	4000	5.0	extra wide lens	2818	45	65
SA28/181040WH-100	102	18294	4000	5.0	extra wide lens	2818	45	65

Please note - Luminaire Lumens will vary slightly for different optics. Please ask for details

## Accessories

Code Suffix	Description	Optic	Description
.../E3	3hr integral maintained emergency	30	Narrow 30° beam
.../DD	DALI control	75	Medium 75° beam
SASK15	Suspension wire, 1.5m drop	90	Wide 90° beam
SA11B	Blank Infil - 1132mm	100	Extra Wide 100° beam
SA14B	Blank Infil - 1413mm	HR	High Rack
SA28B	Blank Infil - 2818mm	DA	Double Asymmetric
SA-PSS	Power supply socket	SAL	Single Asymmetric - Left
SA-EC	End-cap	SAR	Single Asymmetric - Right
RAL	Non-standard colour		